

NÚMERO DE CÓDIGO

34000003

DESCRIPCIÓN

1.1 gpf, Filtered, Brushed Stainless Finish, Fixture Connection Rear Spud, Single Flush, Integrated Control Stop, TruFlush Oculta Manual Sanitario Fluxómetro.

DETALLES

- Volumen de Descarga: 1.1 gpf (4.2 Lpf)
- Acabado: Brushed Stainless (SF)
- Válvula: Pistón
- Sobrepaso: Filtered
- Material del Cuerpo de la Válvula: Latón Semi-rojo
- Tipo de Mueble de Baño: Sanitario
- Conexión del Accesorio: Spud Trasero
- Válvula de Retención: Integrated

CARACTERÍSTICAS

- Piston color-coded by flush volume for easy identification
- Corrosion-resistant, vandal resistant wall plate
- High Efficiency flush volume for water conservation
- Easy to push manual button is ADA compliant. Less than 5 lbf/22N of force required to activate
- Heavy duty brass valve body
- Safety collar locks activation assembly to prevent access of internal components without shutting off water
- Replaceable piston assembly, accessible though front wall plate
- Concealed shut off sleeve adjusts flow rate. Accessible without removing button/bracket assembly
- 1-1/2" NPT (female) Inlet standard
- 1-1/2" NPSM Outlet standard
- Fixed Volume Piston with Filtered O-ring Bypass
- 1.1 gpf (4.2 Lpf) flushometers are only recommended for new construction installations or those where sufficient drain line carry can be assured

VIDEOS

- ▶ TruFlush
- ▶ TruFlush Installation
- ▶ TruFlush Maintenance
- ▶ TruFlush Flush Line

**CUMPLIMIENTOS Y CERTIFICACIONES**

(BREEAM Water Credit, Certificado por UPC, Cumple con BAA, Cumplen con la Ley ADA, EPD, Green Globes Water Credit)

DESCARGAS

- [TruFlush Manual Installation Instructions](#)
- [TruFlush Manual Installation Instructions \(Spanish\)](#)
- [TruFlush Manual Maint Guide](#)
- [Descargas Adicionales](#)

NOTAS

Toda la información contenida dentro de este documento está sujeta a cambio sin previo aviso.

Buscar otras variaciones del TRF 156 producto? [Ver la hoja de especificaciones generales con todas las opciones.](#)

GARANTÍA

[View Warranty Information](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Teléfono: 800.982.5839 • Fax: 800.447.8329 • sloan.com

PREPARACIÓN

NOTE : Flush Connections shown in dotted lines not included.

